



WASHING MACHINE CRATE WASHER FOR AGRICULTURAL INDUSTRY

Machine dimensions LxW (cm): 4400 / 1590 Washing capacity per 1 hour app.: 600 crates Weight dry machine (kg): 530

1.50

1168n** * *

Power supply: 400V

www.precimet.pl

MS-03



WASHING MACHINE CRATE WASHER FOR AGRICULTURAL INDUSTRY

MSO-03 washing machine was designed for industrial crates washing. It features a stand-alone, compact, welded structure enclosed in a housing made of acid-resistant Cr-Ni steel.

The washer consists of the main washing unit with closed water cycle and rinsing unit. The guides situated on both sides keep a crate in the right position during washing. Best washing and hygienic results with easy operation!

Technical specifications

Machine dimensions Weight dry machine Washing capacity per 1 hour Tank capacity Transporting speed Power consumption Power supply

4400/1450/1590 cm 530 kg 600 crates of 5 kg app. 700 l 4,7 m/s 1,22 A 400 V

Main advantages

i jugidi K

i nice

compact design

.

- made of Cr-Ni acid-resistant steel
- washing water closed cycle (saves a lot of water)
- access door to the washing chamber for cleaning the machine
- automatic crates transport (optionary)
- effective washing water filtering system with a system of steel mesh sieves
- washing jets made of acid-resistant steel with a clog-preventing system

Washer

- consists of the main washing unit and rinsing unit
- washing jets are easily dismantled while the construction prevents their clogging
- guides situated on both sides keep a crate in the right position during washing
- crate guides in the washing unit can be easily adjusted to the crates dimensions
- washing jets are also made of stainless steel, which makes them much more durable than plastic jets

Heating unit

- Number of heat: 6 (1+2)
- Power per a heater: 4,5 kW
- Total power: 27,0 kW
- Power supply: 3x230 V
- Adjustable temp.: YES (factory setting: 50 C deg)

Additional information

- Total power: ~33,0 kW
- Protection: IP 44
- Protection class: 1
- Noise level: <=70dB*

*measured 1 m from the machine, at the height of 1.6 m.

- Temperature: + 5°C to + 40°C
- Humidity: <85%
- CE Certificate







Adjustable steel outlet guids

PRECIMET H. C. E. ul. Pomorska 555, 92-735 Łódź, Poland tel.: +48 422 080 422, e-mail: sales@precimet.pl

www.precimet.pl